



ABAC Tech ATF

ATF compressors deliver clean air, which is free of any contamination, thereby avoiding damage to downstream equipment.



- Oil free technology
- Single stage up to 10 Bar
- Proven design with nickel plated aluminium cylinders ensures high durability as pistons are coated with Teflon, to allow lowest friction.

	ATF 2	ATF 3	ATF 5.5	ATF 7.5	ATF 10
V-Hz	400/3/50	400/3/50	400/3/50	400/3/50	400/3/50
Air-end type	Oil free	Oil free	Oil free	Oil free	Oil free
Construction	Industrial	Industrial	Industrial	Industrial	Industrial
kW (hp)	1.5 (2)	2.2 (3)	4 (5.5)	5.5 (7.5)	7.5 (10)
RPM	1500	1500	1500	1500	1500
Cylinders	2	2	2	2	2
Air intake, L/min	408	504	918	1146	1470
FAD L/min (@7Bar)	186	240	492	660	930
Max pressure (Bar)	10	10	10	10	10
Noise db(A)	82	83	83	84	86
Duty cycle	S1 100%	S1 100%	S1 100%	S1 100%	S1 100%
Dimensions (LxWxH) mm	686x530x547	686x530x547	686x530x547	860x591x625	860x591x625
Weight Kg	45	49	90	90	105

Unit performance measured according to ISO 1217, Annex C, latest edition.
Noise level measured according to ISO 2151 2004

